



# 2017 POWER STROKE DIGITAL SWITCH INSTALLATION

PAGE 1

THIS INSTRUCTION MANUAL COVERS INSTALLATION OF THE GAUGE POD MOUNT DSP/SOTF SWITCH FOR 2017 FORD POWER STROKE TRUCKS ONLY.

**DISCLAIMER:** GDP TUNING, LLC WILL NOT BE HELD RESPONSIBLE FOR ANY PERSONAL, PROPERTY, TRUCK, VEHICLE, ENGINE/POWERTRAIN, OR TRANSMISSION DAMAGE/INJURY THAT MAY RESULT WITH THE USE OF THIS MODULE. THIS IS AN AFTERMARKET PART; JUST LIKE ANY OTHER AFTERMARKET PERFORMANCE TRUCK PARTS, INSTALL/USE IT AT YOUR OWN RISK. BE SURE TO USE CAUTION WHEN WORKING AROUND YELLOW CONNECTORS OR WIRING AS THESE CAN BE RELATED TO THE SIR (AIRBAG) SYSTEM.

## STEP 1

ROUTE THE OBD2 SOTF WIRE FROM THE DIGITAL SOTF SWITCH THROUGH THE FIREWALL TO THE APPROPRIATE SENSOR AS SHOWN IN THE PICTURES. BE SURE TO ROUTE THE WIRES CAREFULLY, AWAY FROM HOT SURFACES OR MOVING PARTS. ALSO BE SURE TO SECURE WIRES SO THEY WILL NOT RUB ON ANY SHARP EDGES.

## STEP 2

UNPLUG THE SENSOR AND CAREFULLY CUT BACK APPROXIMATELY 1.5" OF PROTECTIVE WIRE SHEATHING. BE SURE TO NOT CUT INTO THE ACTUAL WIRES WHEN REMOVING THE PROTECTIVE SHEATHING!



## STEP 3

YOUR PINS WILL SLIGHTLY SNAP IN. BE CAREFUL NOT TO BREAK THE LOCKING CLIPS. TUG ON THE WIRE LIGHTLY TO MAKE SURE THEY ARE LOCKED IN.



## STEP 4

THE RED SOTF WIRE FROM THE SWITCH TO THE GREEN WIRE ON THE SENSOR.





# 2017 POWER STROKE DIGITAL SWITCH INSTALLATION

PAGE 2

---

## PROGRAMMING/SETUP PROCEDURE

**NOTE:** THE SWITCH IS SET TO A DEFAULT MODE FROM THE FACTORY AND MUST BE CONFIGURED/SETUP FOR YOUR PARTICULAR TRUCK.

THE **"UP"** ARROW IS FOR CONFIGURING THE YEAR/ENGINE OF TRUCK.

THE **"DOWN"** ARROW IS FOR CONFIGURING THE SWITCH WAKE-UP/SLEEP SOURCE

## TRUCK YEAR/ENGINE CONFIGURATION

### STEP 1

PRESS AND HOLD THE **UP** ARROW OF THE SWITCH. WHILE HOLDING THE **UP** ARROW BUTTON **PLUG IN** THE OBD2 PLUG FROM THE SWITCH. THE SWITCH WILL POWER ON AND SHOW **P** (PROGRAM). ONCE IT SHOWS **P**, YOU CAN RELEASE THE **UP** ARROW.

### STEP 2

THE SWITCH DISPLAY WILL THEN SHOW EITHER **"H"**, **"1"**, OR **"2"** FOR A FEW SECONDS, GO BLANK FOR A SECOND, THEN RETURN TO REGULAR OPERATION. **"H"** IS 2001-2005 LB7/LLY DURAMAX, **"1"** IS 2006-2010 LBZ/LMM DURAMAX, **"2"** IS 2011-2016 LML DURAMAX AND FORD SUPERDUTY 11-17

### STEP 3

EACH TIME PROGRAMMING MODE IS MANUALLY ENTERED (**FOLLOWING STEPS 1-3**), THE SETTING WILL STEP UP ONE LEVEL (**H, 1, 2**), AND THEN LOOP BACK AROUND TO **"H"**. ONCE YOU HAVE FOLLOWED STEPS 1-3 THE APPROPRIATE AMOUNT OF TIMES TO GET THE **"P"** SETTING TO **H** (LB7/LLY), YOU CAN TURN THE IGNITION OFF, WAIT A FEW SECONDS, AND THE YEAR SETTING WILL BE SAVED. YOU CAN RE-ENTER PROGRAMMING MODE (OR EXAMPLE, IF YOU ARE REMOVING AND INSTALLING THE SWITCH ON A DIFFERENT TRUCK) AT ANY TIME BY FOLLOWING STEPS 1-3.

---

## SWITCH WAKE-UP/SLEEP SOURCE

THIS PROGRAMMING MODE IS TO SETUP THE SWITCH FOR AUTOMATIC ON/OFF BASED ON **CAN** BUS ACTIVITY. WHEN CAN TRAFFIC IS DETECTED BY THE SWITCH (**IE, WHEN THE IGNITION IS TURNED ON**), THE SWITCH WAKES UP AND TURNS ON. WHEN CAN TRAFFIC STOPS (**IE, TRUCK IS SHUT OFF**), THE SWITCH WILL WAIT AN EXTRA **~10 SECONDS**, AND THEN PUT ITSELF TO SLEEP SO AS NOT TO DRAIN THE TRUCKS BATTERY.

THE TWO SETTINGS ON THE SWITCH ARE **"C"** FOR **CAN** BUS WAKE UP/SLEEP, AND **"D"** FOR **DISCRETE** WAKEUP/SLEEP SOURCE. THE **"D"** DISCRETE POWER SETTING IS **ONLY** FOR 2001-2005 DURAMAX THAT DOES NOT HAVE CAN PINS WIRED INTO THE OBD PORT AND THUS CANNOT BE SWITCHED ON/OFF AUTOMATICALLY. **"D"** DISCRETE SETTING FOR 2001-2005 DURAMAX SIMPLY TURNS THE SWITCH ON/OFF WITH THE IGNITION KEY.

### STEP 1

PRESS AND HOLD THE **DOWN** ARROW OF THE SWITCH. WHILE HOLDING THE **UP** ARROW BUTTON PLUG IN THE OBD2 PLUG FROM THE SWITCH.

### STEP 2

THE SWITCH WILL POWER ON AND SHOW THE CURRENT SWITCH WAKE/SLEEP SOURCE. **"D"** (**DISCRETE, 01-05 DURAMAX ONLY**) OR **"C"** (**CAN, 2006+ DURAMAX AND FORD**). THE SWITCH DISPLAY WILL THEN GO BLANK FOR A SECOND, THEN RETURN TO REGULAR OPERATION.

### STEP 3

IF THE SWITCH SHOWS **D**, AND RETURNS TO NORMAL OPERATION, THE SWITCH IS CONFIGURED PROPERLY.

### STEP 4

TO SELECT THE CORRECT SETTING FOR SWITCH WAKE-UP. **REPEAT** STEPS 1-3

### STEP 5

DOUBLE CHECK ON/OFF OPERATION OF THE SWITCH, WITH THE KEY **ON**, THE SWITCH SHOULD BE ON, AND THE SWITCH SHOULD THEN TURN OFF AS SOON AS THE KEY IS TURNED **OFF**.

## SETUP COMPLETE

DOUBLE CHECK ALL CONNECTIONS, SECURE/TAPE ANY EXTRA WIRE, REINSTALL TRIM PANELS, AND ENJOY YOUR GDP TUNING GAUGE POD DIGITAL DSP/SOTF SWITCH!



# 2017 POWER STROKE DIGITAL SWITCH INSTALLATION

PAGE 3

## HIGH IDLE INSTALLATION

THE DIGITAL SOTF SWITCH ALSO HAS THE ABILITY TO ENABLE MANUAL HIGH-IDLE ON THE 6.7 POWERSTROKE. THIS INSTALL IS OPTIONAL, IF YOU DO NOT WISH TO INSTALL HIGH IDLE, SKIP THE FOLLOWING STEPS AND IGNORE THE REMAINING FOUR WIRES ON THE SOTF SWITCH HARNESS.

### STEP 1

FOLLOWING THE PICTURE, LOCATE THE SEIC PASS-THROUGH WIRES UNDER THE DASH, NEAR THE OBD PORT.

-BLUNT-CUT ACCESS WIRES FOR SEI, "CUSTOMER ACCESS" SIGNAL CIRCUITS FOR CTO,VS\_OUT,PARK TRO-N, & 4 PASS-THRU WIRE, ARE BUNDLED TOGETHER AT THE HARNESS ABOVE THE PARKING BRAKE PEDAL ASSEMBLY BEHIND THE DATA LINK CONNECTOR.

F250/350/450/550  
PASSENGER SIDE /KICK PANEL



### STEP 2

LOCATE THE **YELLOW/GREEN** WIRE ON THE TRUCKS SEIC PASS-THROUGH HARNESS IN **PIN 7**. SPLICE THE **BLUE** WIRE FROM THE **DIGITAL SWITCH** TO THE **YELLOW/GREEN** WIRE IN **PIN 7** ON THE **TRUCK**.

### STEP 3

LOCATE THE **GREEN** WIRE ON THE **DIGITAL SWITCH**. SPLICE THE **GREEN** WIRE FROM THE **DIGITAL SWITCH** TO THE **GREEN** WIRE ON THE **TRUCK**.

## HIGH IDLE MODE

THE GAUGE POD DIGITAL DSP/SOTF SWITCH ALSO HAS A MANUAL HIGH IDLE MODE FOR FASTER WINTER WARM UP, JUMP STARTING OTHER VEHICLES, ETC. TO ACTIVATE THE HIGH IDLE MODE, THE TRUCK MUST BE IN PARK AND YOUR FOOT MUST BE OFF THE BRAKE PEDAL. PRESS THE "**DOWN**" ARROW SEVERAL TIMES UNTIL THE SWITCH DISPLAY SHOWS "**1**". WHEN THE DISPLAY SHOWS "**1**", PRESS AND HOLD THE "**DOWN**" ARROW FOR ~3 SECONDS, AND THE DISPLAY WILL CHANGE TO "**H**" (HIGH IDLE). (**PARK BRAKE HAS TO BE SET**)

ONCE THE DISPLAY CHANGES TO "**H**", THE ENGINE WILL GO TO THE BASE HIGH IDLE OF ~900RPM. TO INCREASE HIGH IDLE RPM, PRESS THE "**DOWN**" ARROW. WITH EACH SUCCESSIVE PRESS OF THE "**DOWN**" ARROW, THE ENGINE WILL STEP UP THROUGH 5 DIFFERENT HIGH IDLE RPM PRESETS (~1100, ~1500, ~1800, ~2100, ~2600).

TO EXIT HIGH IDLE MODE, PRESS THE "**UP**" ARROW, OR PRESS THE BRAKE PEDAL.



# 2017 POWER STROKE DIGITAL SWITCH INSTALLATION

PAGE 4

